



CNT-PROFI PROFIBUS Connector

PROFIBUS (PROCESS FIELD BUS) which is anchored in the international standards IEC 61158 and IEC 61784 is an open, digital communication system with a wide range of applications, particularly in the fields of factory and process automation. The CNT-PROFI connector is used to connect a PROFIBUS node to the PROFIBUS line featuring quick-connect technology, making the stripping of bus conductors superfluous. The connector is quick to install, and has a plastic housing and integrated terminating resistors. Anyway the CNT-PROFI could link a PROFIBUS device to a PROFIBUS line easily and fast.



Applications

PROFIBUS DP Master



CNT-PROFI

GW-7553
PROFIBUS/Modbus Gateway



CNT-PROFI

PROFI-8455
PROFIBUS I/O Unit



CNT-PROFI

PROFI-5000 Series
PROFIBUS Remote I/O Module



CNT-PROFI

PROFIBUS Network

Features

- Built-in switch to select terminal resistor.
- 2 cable entries.

Hardware Specifications

Cable outlet	90° cable outlet
Connector	9-pin, D-Sub male connector
Baud rate	9.6kbps ~ 12Mbps
Operating temperature	-25° ~ 75°
Storage temperature	-30° ~ 80°
Humidity	10 ~ 90% RH, non-condensing

Ordering Information

CNT-PROFI	PROFIBUS Connector
------------------	--------------------