



I-87018W

I-87018W

8-channel Thermocouple Input Module

Specifications

Analog Input	
Input Channels	8 Differential
Input Type	+/- 15mV, +/- 50mV, +/- 100mV +/- 500mV, +/- 1V, +/- 2.5V -20mA ~ +20mA(Requires Optional External 125 Ohm Resistor) Thermocouple(J, K, T, E, R, S, B, N, C, L, M, LDIN43710)
Resolution	16-bit
Sampling Rate	10 Samples/ sec (Total)
Accuracy	+/- 0.1% of FSR
-3dB BandWidth	15.7Hz
Zero Drift	+/- 0.5µV °C
Span Drift	+/- 25 µV/ °C
Common Mode Rejection	150 dB
Normal Mode Rejection	100 dB
Input Impedance	20M Ohms
Open Thermocouple Detection	No
Overvoltage Protection	-35V to +35V
4KV ESD Protection	Yes, Contact for each terminal
Intra-module Isolation, Field to Logic	3000VDC
LED Display	
1 LED as Power/ Communication Indicator	
Power	
Power Consumption	Maximum: 0.8W
Environment	
Operating Temperature	-25 to 75 °C
Storage Temperature	-30 to 75 °C
Humidity	5 to 95%, Non-condensing
Dimensions	
31 x 81 x 114 (W x D x H)	
Note : We recommend to choose I-87018Z for accurate thermocouple measurement.	

RTD Temperature Range

Type	Range °C
J	-210~ +760
K	-270~+1372
T	-270~+400
E	-270~+1000
R	0~+1768
S	0~+1768
B	0~+1820
N	-270~1300
C	0~2320
L	-200~+800
M	-200~+100
L2(DIN43710)	-200~+900

Ordering information

I-87018W-G CR

8-channel Thermocouple Input Module (Gray Cover) (RoHS)