

Серия	i							iE										XE				eMT						
Модель	6050i	6070iH	6100i	8050i	8070iH	8100i	8104iH	8050iE	6070iE	6071iE	8070iE	8071iE	8073iE	8070iER	8100iE	8101iE	8102iE	8103iE	8090XE	8092XE	8121XE	8150XE	3070B	3105P	3120A	3150A		
Программное обеспечение																												
ПО для программирования	EasyBuilder 8000							EasyBuilder Pro										EasyBuilder Pro				EasyBuilder Pro						
EasyAccess 2.0	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	встроен	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Встраивание в проект изображений	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Встраивание в проект информации ПЛК тегов	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Рецептурная база данных	-	-	-	-	-	-	-	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Просмотр базы данных	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Журнал учета работы	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Расширенная безопасность	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Защита проекта	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
e-Mail	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Медиа Плеер	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
USB камера	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
CAN bus	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
VNC	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Аппаратная часть																												
Экран	4.3"	7"	10.1"	4.3"	7"	10.1"	10.4"	4.3"	7"	7"	7"	7"	7"	7"	10.1"	10.1"	10.1"	10.1"	9.7"	9.7"	12.1"	15"	7"	10.4"	12.1"	15"		
Разрешение	480x272	800x480	480x272	800x480	800x600	480x272	800x480	480x272	16.7M	16M	16.7M	262K	1024x600	1024x768	800x480	800x600	1024x768	262K	16.2M	16.7M	262K	16.2M	16.7M	262K	16.2M	16.2M		
Количество цветов	65536							16M							16.7M							262K						
Flash память (MB)	128							128							256							256						
RAM (MB)	64							128							256							256						
CPU	ARM9 32-бит, 400 МГц							Cortex A8 32-бит, 600МГц										Cortex A8 32-бит, 1ГГц				Cortex A8 32-бит, 1ГГц	Cortex A8 32-бит, 800МГц					
Слот SD Card	-	-	✓	-	✓	✓	✓	-	-	-	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓		
USB Host	USB 1.1	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
	USB 2.0	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
USB Client 2.0	✓	✓	✓	-	✓	✓	✓	-	✓	✓	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓		
Ethernet 10/100TX	-	-	-	✓	✓	✓	✓	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	✓	✓	✓	✓	✓	✓		
Ethernet 10/100/1000TX	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	✓	-	-	-	-	-	-		
WiFi	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
COM1	RS-232	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	✓	✓	✓	✓		
	RS-232/RS-485 (2w/4w)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	✓	✓	✓	✓	✓	✓		
COM2	RS-232	-	✓	✓	-	✓	✓	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
	RS-485 (2w/4w)	-	-	-	-	-	-	-	-	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-	-	-	-		
COM3 (2W)	RS-232/RS-485	-	✓	✓	-	✓	✓	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	-	✓	-	-	✓	✓	✓	✓		
	RS-485	✓	-	-	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	✓	✓	-	-	-	-		
Изоляция RS-485	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓		
Аудио, линейный выход	-	-	-	-	✓	✓	✓	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Часы реального времени (RTC)	-	✓	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Вес (кг)	0.3	0.85	1.4	0.3	0.85	1.4	1.6	0.25	0.6			0.52	1.3	1	0.85	2.1	2.75	0.9	1.6	2.1	2.75	0.9	1.6	2.1	2.75			
Защита передней панели	IP65 NEMA4							IP65 NEMA4										IP65 NEMA4				IP66 NEMA4						
PCB защитное покрытие	-	-	-	✓	✓	✓	✓	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Корпус	Пластиковый							Пластиковый										Пластиковый				Металлический	Пластиковый			Металлический		
Размер выреза под панель (мм)	119 × 93	192 × 138	260 × 202	119 × 93	192 × 138	260 × 202	259 × 201	119 × 93	192 × 138			260 × 202	248.5 × 191	305 × 231	352 × 279	192 × 138	259 × 201	305 × 231	352 × 279									

\* MT8073iE/ MT8102iE/ MT8103iE: Для COM1 RS-232 может быть использован только Tx & Rx (не RTS/CTS) в момент, когда так же используется COM3 RS-232